

12/15W - KS-MD02D-B-412

Simple but exquisite, our mounted downlight combines aesthetic features and performance. A variety of choices and customized services depending on your requirements. A professional design with high quality optical materials including an AL1090 aluminum reflector for COB and a fire rated PC for SMD ensures high light transmission, uniform light beam and excellent light quality. even and soft light offers a desirable lighting atmosphere.

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	130mm*100mm*1500mm
Installation	Pendent Mounted
Beam Angle	90°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	3 Years

Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	12 W 15 W
Exit Lumens	960 lm 1200 lm
Efficiency	80.0 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	12W - 960 lm, 15W - 1200 lm
Colour	3000K, 4000K, 5000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable

Product Code: 12/15W - KS-MD02D-B-412