

LED UK

30/35/40W KAS-TL13R-A-1130

Flexible lines,without losing the texture. The heatsink cap adopts Hexagonal honeycomb-shaped, like the texture on the dress. Continous and precise directional adjustment (Horizontal 350° and Vertical 90°) Rapid replacement between optical accessories and anti-glare accessories.The outer ring could be tighten and fixed by 40 ° clockwise , but turned on by counterclockwise

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

| | |
|---------------|---------------------------------|
| Dimensions | 115*165*215mm |
| Installation | Track Lighting |
| Beam Angle | 15° 24° 30° 36° 60° |
| Voltage | AC220-240V |
| Certification | CE, ROHS |
| Warranty | 5 Years |

Performance

| | |
|------------------|---|
| Colour Rendering | Ra>80/90 |
| Longevity | 50,000 hours |
| System Power | 30 W 35 W 40 W |
| Exit Lumens | 2700 lm 3150 lm 3600 lm |
| Efficiency | 90.0 ll/cW |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating |

LED UK

30/35/40W KAS-TL13R-A-1130

Available options

| | |
|-------------|---|
| Wattage | 30W - 2700 lm, 35W - 3150 lm, 40W - 3600 lm |
| Beam Angle | 15°, 24°, 30°, 36°, 60° |
| Colour | 3000K, 4000K, 5000K |
| Base Colour | White, Black, Iron Gray |
| Dimming | Fixed Output, 1-10V Dimming, DALI Dimmable |

Product Code: 30/35/40W KAS-TL13R-A-1130