

LED UK

30/35/40W KAS-TL13R-B-1130

Flexible lines,without losing the texture. The heatsink cap adopts Hexagonal honeycomb-shaped, like the texture on the dress. Continous and precise directional adjustment (Horizontal 350° and Vertical 90°) Rapid replacement between optical accessories and anti-glare accessories.The outer ring could be tighten and fixed by 40 ° clockwise , but turned on by counterclockwise

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	115*165*198mm
Installation	Track Lighting
Beam Angle	15° 24° 30° 36° 60°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>80/90
Longevity	50,000 hours
System Power	30 W 35 W 40 W
Exit Lumens	2700 lm 3150 lm 3600 lm
Efficiency	90.0 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating

30/35/40W KAS-TL13R-B-1130

Available options

Wattage	30W - 2700 lm, 35W - 3150 lm, 40W - 3600 lm
Beam Angle	15°, 24°, 30°, 36°, 60°
Colour	3000K, 4000K, 5000K
Base Colour	White, Black, Iron Gray
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable

Product Code: 30/35/40W KAS-TL13R-B-1130