Page 1/2

an 1/0

The Alta Mini Frosted LED is a 90mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The bezel features a 40mm recess detail creating a glare friendly cut-off which is also an aesthetically pleasing architectural detail. The Alta Mini Frosted is available in a 675lm outputs with 15°, 24°, 30° and 36° beam angle options and is

rated IP20.

Alta Mini Frosted

CREE LED Engine

LEDUK

- Cast Aluminium
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

| Dimensions | Ø90mm x 100mm |
|---------------|------------------------------|
| Cutout | Ø80mm |
| Weight | 0.2kg |
| Installation | Ceiling Tile Plasterboard |
| Voltage | 220-240Vac |
| Certification | CE, ROHS |
| Warranty | 5 Years |




Colour Rendering

Ra>82

| Longevity | 50,000 hours | |
|--------------|--|--|
| System Power | 10 W | |
| Exit Lumens | 675lm | |
| Efficiency | 67.5 II/cW | |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating | |







Available options

| Wattage | 10W - 675lm |
|--------------------|---|
| Colour | White, Special RAL Colour |
| Colour Temperature | 3000K, 4000K, 5000K |
| Beam Angle | 15° Beam, 24° Beam, 30° Beam, 36° Beam |
| Lens | Frosted |
| Dimming | Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming |
| Emergency | Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test |

Product Code: ALT-M-F