

Ameraz Glow

The Ameraz Glow Wall LED panel is a luminaire specifically designed for circulation areas with a suitable backlit glow. The body is constructed from powder coated steel & the diffuser is made from high efficiency PMMA which gives the luminaire optimum performance. The Ameraz has a lifespan of over 50,000 hours and produces an efficacy of 114 lm/W.

- Architectural appearance
- High transmittant frosted lens
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	150 x 580 x 90mm
Weight	2.8 kg
Installation	Surface Wall Mounted
Voltage	220-240Vac 50/60Hz
Warranty	5 Years



Performance

Colour Rendering	Ra>80
UGR	<19
System Power	15 W
Exit Lumens	2500 lm
Efficiency	166.7 ll/cW
Longevity	50,000 hours
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Colour Temperature	3000K, 4000K, 5000K
Dimming	Fixed output, 1-10V Dimming, DALI Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: ARG