

## Brite + 600 x 600


 $600 \times 600$  lay in, back lit , recessed LED Modular with opal diffuser which as part of the Brite Range, compliments the  $1200 \times 300$  and  $300 \times 300$  LED Brite + Modular fittings . The luminaire is designed for lift and tilt installation onto a 15mm Tee Grid or a 24mm Tee Grid. The Brite +  $600 \times 600$  lay in modular fitting is also suitable for an offer up installation into a plasterboard ceiling. The Brite +  $600 \times 600$ mm LED panel light is an environmentally friendly LED solution assembled from injection moulded ABS. The diffuser is constructed from high efficiency PMMA which provides a highly uniformed, low glare and dot free distribution of light.




- Architectural appearance screwless smooth bezel
- · High transmittant frosted lens
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- · Remote control gear

#### General

Dimensions	595 x 595 x 42mm
Weight	2.5kg
Installation	Recessed 24mm T-Grid Recessed Burgess Recessed Plasterboard
Voltage	85-265Vac 50/60Hz
Certification	SAA, TUV, CE, GS, CB, ERP
Warranty	5 Years
IP Rating	IP44





### **Performance**

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	28.9 W
Exit Lumens	3532 lm
Efficiency	122.3 II/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



# Brite + 600 x 600

## **Available options**

Colour Temperature	3000K, 4000K, 6000K
<b>Mounting Option</b>	Lift and tilt, Offer up
Dimming	Fixed output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming, DSI Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

**Product Code: BRP-06X06**