LEDUK

Brite High Output


 600×600 lay in, back lit, recessed LED Modular with opal diffuser with an increased lumen performance. The luminaire is designed for lift and tilt installation onto a 15mm Tee Grid or a 24mm Tee Grid. The Brite High Output 600×600 lay in modular fitting is also suitable for an offer up installation into a plasterboard ceiling. The High Output Brite 600×600 mm LED panel light is an environmentally friendly LED solution assembled from injection moulded ABS. The diffuser is constructed from high efficiency PMMA which provides a highly uniformed, low glare and dot free distribution of light.




- Architectural appearance screwless smooth bezel
- High transmittant frosted lens
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- · Remote control gear

General

Dimensions	595 x 595 x 52mm
Weight	2.8kg
Installation	Recessed 24mm T-Grid Recessed Burgess Recessed Plasterboard
Voltage	85-265Vac 50/60Hz
Certification	SAA, TUV, CE, GS, CB, ERP
Warranty	5 Years
IP Rating	IP44





Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	45.3 W
Exit Lumens	5,403 lm
Efficiency	119.2 II/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Colour Temperature	3000K, 4000K, 6000K
Mounting Option	Lift and tilt, Offer up
Dimming	Fixed output, 1-10V Dimming, DALI Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: BRH-06X06