

## CI Series - 3.125 mm Pixel Pitch

### 3.125 mm Pixel Pitch, Indoor LED Screen Display

- Seamless Mosaic Technology - Picture of high uniformity without gaps and information missing, ensuring real seamless mosaic effect
- Intelligent Brightness Self-adjusting System Brightness of the screens can be adjusted intelligently according to the ambient light level
- Real and Natural Colour - Leading calibration technology is applied with advanced color reproduction function to offer a real and natural color that is completely complied with human eyes' visual habit.
- Large Viewing Angle - Broad viewing angle up to 140°, bringing a larger visible viewing area
- LCD Intelligent Control - Intelligent Control, indicating the exact accumulated working hours and temperature of cabinet



<b>Model</b>	<b>CI-SC-3.125</b>
<b>Pixel Pitch (mm)</b>	3.125
<b>Physical Density (dot/m<sup>2</sup>)</b>	102,400
<b>LED Configuration</b>	1R1G1B
<b>Module Size (mm x mm)</b>	200 x 100
<b>Module Resolution (PX x PX)</b>	64 x 32
<b>Cabinet Power Consumption (w)</b>	25
<b>Drive Mode</b>	Constant Current Drive
<b>Horizontal Viewing Angle (Deg)</b>	140
<b>Vertical Viewing Angle (Deg)</b>	140
<b>Brightness (cd/m<sup>2</sup>)</b>	900
<b>Grey Scale</b>	14 Bit
<b>Refresh Rate (Hz)</b>	>1600
<b>Cabinet Resolution (PX xPX)</b>	128 x 128
<b>Cabinet Max Power Consumption (w)</b>	300
<b>Cabinet Avg Power Consumption (w)</b>	80
<b>Cabinet Size (mm x mm)</b>	400 x 400
<b>Cabinet Thickness (mm)</b>	93
<b>Cabinet Material</b>	Aluminium
<b>Colour</b>	281tn

# LED UK

## CI Series - 3.125 mm Pixel Pitch

---

Input Voltage (v)	96-264(VAC)
Protection Level	IP43
Refresh Frame Frequency (hz)	50-60
Working Environment	Indoor
Working Temperature (°C)	-20°C ~ +40°C (operating)
Operation Humidity (RH)	10% ~ 85% (operating)
Life Span (H)	100,000 hrs
Certificates	CCC    CE

**Product Code: CI-SC-3.125**