

The Connex is a 130mm diameter downlight which utilises a Philips LED Module. The heatsink is constructed from die-cast aluminium complete with a either a white or brushed aluminium bezel. The heatsink features sprung arms which allows the fitting to be installed with ease.

- Philips LED Module
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



### General

<b>Dimensions</b>	Ø130 x 99mm
<b>Cutout</b>	Ø110mm
<b>Weight</b>	1.3kg
<b>Beam Angle</b>	40°
<b>Installation</b>	Ceiling Tile Plasterboard
<b>Voltage</b>	220-240Vac
<b>Certification</b>	CE, ROHS
<b>Warranty</b>	5 Years
<b>IP Rating</b>	IP54

### Performance

<b>Colour Rendering</b>	Ra>80
<b>Longevity</b>	L80 / B20 @ 50,000 hours
<b>System Power</b>	18W
<b>Exit Lumens</b>	1950 Lm
<b>Efficiency</b>	108 lm/cW
<b>Compliance</b>	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

### Available options

<b>Wattage</b>	18W
<b>Base Colour</b>	Aluminium (Brushed), White
<b>Colour Temperature</b>	2700K, 3000K, 4000K, 5000K
<b>Lens</b>	Clear
<b>Dimming</b>	Fixed Output, DALI
<b>Emergency</b>	Not Required, 3 Hour Facility, 3 Hour Central Test

**Product Code: CNX-S**