## LEDUK

## **Disc**

The Disc LED is a large area circular luminaire with a maximum thickness of 16mm creating a striking appearance. The fitting is available in diameters of 450mm & 600mm and can be surface or suspended mounted. The surface version has an LED backlighting kit which creates a halo effect on the ceiling. The body is made from aluminium the diffuser is opal polycarbonate. Other custom sizes are available on request.




- 16mm maximum thickness
- Aluminium body
- Polycarbonate diffuser
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



Dimensions	Ø450 x 16mm Ø600 x 16mm
Weight	3.6 kg 4.8 kg

Installation	Ceiling Surface Ceiling Suspended
Voltage	90-250Vac 50/60Hz
Certification	CE, ROHS
Warranty	3 Years



#### **Performance**

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	37.8 W 50.4 W
Exit Lumens	3,202 lm 4,043 lm
Efficiency	84.7 II/cW 80.2 II/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



# Disc

## **Available options**

Size	Ø450 (35W), Ø600 (50W)
<b>Colour Temperature</b>	3000K, 4000K, 6000K
<b>Mounting Option</b>	Surface, Suspended
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming

**Product Code: DSC**