Page 1/2

 CREE LED Engine Cast Aluminium Instant on - no flicker Environmentally Friendly - No mercury or lead enters the environment No RF and electronic magnetic interference Over 50,000 hours life span 		
Dimensions	Ø130 x 155mm	
Cutout	Ø120mm	
Installation	Ceiling Tile Plasterboard	
Beam Angle	15°	

Gene

Cutout Installa Beam A ıg 24° 30° 36° 45° Voltage AC220-240V Certification CE, ROHS Warranty 5 Years

Performance

Colour Rendering	Ra>80/90
Longevity	50,000 hours
System Power	12 W 15 W 20 W 25 W
Exit Lumens	960 lm 1,200 lm 1,600 lm 2,000 lm
Efficiency	80.0 II/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating

mm - 155

6.







The Draco Fixed Range is a high power COB Downlight with double reflector design which will give you a clear, strong light without glare, it is available with 15°, 24°, 30°, 36° and 45° beam angles.

- ٠
- •

Available options

Wattage	12W - 960 lm, 15W - 1200 lm, 20W - 1600 lm, 25W - 2000lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 5000K
Beam Angle	15° Beam, 24° Beam, 30° Beam, 36° Beam, 45° Beam
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: DRC-F-S