#### Page 1/1

## **Product Code: ECO**

| The Echo LED is a 300mm diameter surface wall/ceiling luminaire constructed from die      |
|---|
| cast aluminium. Rated IP65 & IK10 providing an aesthetic look with vandal resistance.     |
| The luminaire available in 20, 30 or 40 Watts. The light distribution is symmetrical with |
| an even halo light effect.  |

- Cast Aluminium
- IP65 rated

LEDUK

Echo

- IK10 rated
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

### General

| Dimensions    | Diameter 300mm Height 87mm |
|---------------|----------------------------|
| Weight        | 1.7kg                      |
| Installation  | Wall/Ceiling Surface       |
| Voltage       | AC85V-265V 50/60Hz         |
| Certification | CE, ROHS                   |
| Warranty      | 5 Years                    |
| IP Rating     | IP65                       |
| Impact Rating | IK10                       |

#### Performance

| Colour Rendering | Ra>80  |
|------------------|--|
| Longevity        | 50,000 hours   |
| System Power     | 20W / 30W / 40W  |
| Exit Lumens      | 1600lm / 2400lm / 3200lm   |
| Efficiency       | 80.0 I/W   |
| Compliance       | Building Regulations<br>ETL (Energy Technology List)<br>ECA (Enhanced Capital Allowance)<br>SKA Rating |
|                  |  |

# **Available options**

| Wattage            | 20W - 1600Lm, 30W - 2400Lm, 40W - 3600Lm  |
|--------------------|---|
| Colour Temperature | 3000K, 4000K  |
| Body               | White Painted Finish, Black Painted Finish  |
| Microwave Sensor   | No Microwave Sensor, Microwave Sensor   |
| Dimming            | Fixed Output, 1-10V, DALI Dimming, Switch Dimming   |
| Emergency          | Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour<br>Central Test, 3 Hour Central Battery |

