

Edge Mini Track

The Edge Mini Track LED is a 47mm diameter tracklight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium housing and reflector. The luminaire is constructed from die cast aluminium and has a 350° swivel arm. The body can rotate 180° from the swivel arm. The Edge Mini Track is available in 412lm and 660lm outputs with 10°, 15°, 24° and 36° beam angle options. The downlight is supplied with an open anti dazzle reflector as standard.

- CREE LED Engine. SDCM<3
- Cast Aluminium
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	Ø47 x 107 x 129mm
Swivel	350°
Weight	0.3kg
Installation	Track Integration
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years

Performance

	SKA Rating
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance)
Efficiency	82 II/cW
Exit Lumens	412lm 660lm
System Power	5W 8W
Longevity	50,000 hours
Colour Rendering	Ra>92

Available options

Wattage	5W - 412lm, 8W - 660lm
Body Finish	White, Black
Colour Temperature	3000K, 4000K, 5000K
Beam Angle	10°, 15°, 24°, 30°, 36°
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimmable, Switch Dimming

Product Code: EDG-M-T