LEDUK FO Series - 18.75 mm Pixel Pitch

18.75 mm Pixel Pitch, Outdoor LED Curtain

- FO Series only weighs 22kg/m2 while the traditional outdoor screen is normally 60kg/m2, the weight of which is decreased by 63%
- The installation just needs a location for the installation of frame instead of heavy steel structure, which can significantly reduce the load-bearing of buildings
- Self heat dissipation excludes the demand for air conditioning, saving power and expense
- The porous design can fulfill air convection and protect the screen against strong wind
- Single cabinet can be directly dismantled from the frontage of the screen, easy to maintain
- The permeability can reach 40-70% according to different distance so it won't influence the lighting inside the building
- High brightness and waterproof IP66

Model	FO-SC-18.75
Pixel Pitch (mm)	18.75
Physical Density (dot/m ²)	2,844
LED Configuration	1R1G1B
LED Type	DIP346
Module Size (mm x mm)	12 x 1,200
Module Resolution (PX x PX)	1 x 64
Power Consumption (W)	12
Drive Mode:	Static Constant Current
Horizontal Viewing Angle (Deg)	90
Vertical Viewing Angle (Deg)	45
Brightness (cd/m ²)	8,000
Grey Scale	16 Bit
Refresh Rate (Hz)	>1,500
Cabinet Resolution (PX x PX)	32 x 64
Cabinet Max Power Consumption (W)	400
Cabinet Avg Power Consumption (W)	160
Cabinet Size (mm x	600 x 1,200

	THE OWNER AND ADDRESS OF THE OWNER
	Contraction of the local division of the loc
The second s	
And a second s	
the second s	A REAL PROPERTY AND ADDRESS OF A DESCRIPTION OF
and the second	CONTRACTOR OF THE OWNER OWNER OF THE OWNER
No. of Concession, Name of	Contraction of the second s
the second s	The second s
	THE REAL PROPERTY OF THE PROPERTY OF THE REAL PROPE
The second	
	THE REAL PROPERTY OF THE PARTY
	and the second se
	The second
the second se	and the second state of th
The second se	
	THE REPORT OF A DESCRIPTION OF A DESCRIP
Contract of the local division of the local	
Contraction of the second s	
the second se	
Contraction of the second s	The second se
of the local division of the local divisiono	
	and and a second s
the second se	
CONTRACTOR OF THE OWNER OWNER OF THE OWNER OWNE	and the second
the second se	And a second
	And a state of the
	The second s

LEDUK FO Series - 18.75 mm Pixel Pitch

mm)	
Cabinet Weight (Kg)	17.5
Cabinet Thickness (mm)	88
Cabinet Material	Aluminium
Colour	281tn
Input Voltage	AC 85V~250V +/- 10%
Refresh Frame Frequency (Hz)	50/60
Protection Level	IP66
Working Environment	Outdoor
Working Temperature (°C)	-20 ~ +45
Operation Humidity (RH)	10%-90%
Life Span (H)	100,000
Certificates	CE

Product Code: FO-SC-18.75