LEDUK FO Series - 25.0 mm Pixel Pitch

25.0 mm Pixel Pitch, Outdoor LED Curtain

- FO Series only weighs 22kg/m2 while the traditional outdoor screen is normally 60kg/m2, the weight of which is decreased by 63%
- The installation just needs a location for the installation of frame instead of heavy steel structure, which can significantly reduce the load-bearing of buildings
- Self heat dissipation excludes the demand for air conditioning, saving power and expense
- The porous design can fulfill air convection and protect the screen against strong wind
- Single cabinet can be directly dismantled from the frontage of the screen, easy to maintain
- The permeability can reach 40-70% according to different distance so it won't influence the lighting inside the building
- High brightness and waterproof IP66

Model	FO-SC-25
Pixel Pitch (mm)	25
Physical Density (dot/m ²)	1,600
LED Configuration	1R1G1B
LED Type	DIP346
Module Size (mm x mm)	12 x 1,200
Module Resolution (PX x PX)	1 x 48
Power Consumption (W)	10
Drive Mode:	Static Constant Current
Horizontal Viewing Angle (Deg)	90
Vertical Viewing Angle (Deg)	45
Brightness (cd/m ²)	6,500
Grey Scale	14 Bit
Refresh Rate (Hz)	>1,500
Cabinet Resolution (PX x PX)	24 x 48
Cabinet Max Power Consumption (W)	400
Cabinet Avg Power Consumption (W)	120
Cabinet Size (mm x	600 x 1,200

The second se	The second s
the second se	
the second s	The second se
and the second se	THE REAL PROPERTY OF THE PROPERTY OF THE REAL PROPE
and the second se	
	the state of the s
	CONTRACTOR OF A CONTRACTOR OF
	THE REAL PROPERTY OF THE PROPERTY OF THE REAL PROPE
	And a state of the
	AND DESCRIPTION OF A DE
	And a state of the
the second s	And a state of the
The state of the s	and the second se
	The second s
	the second se
	The second s
the second se	And and a second s
	THE REPORT OF TH
	And the second se
	and the second se
Contraction of the second s	and the second se
and the second se	and the second se
	and the second se
the second se	and the second se
	And a second
The second se	
and the second se	
the second s	
	the second s

LEDUK FO Series - 25.0 mm Pixel Pitch

mm)	
Cabinet Weight (Kg)	15
Cabinet Thickness (mm)	88
Cabinet Material	Aluminium
Colour	281tn
Input Voltage	AC 85V~250V +/- 10%
Refresh Frame Frequency (Hz)	50/60
Protection Level	IP66
Working Environment	Outdoor
Working Temperature (°C)	-20 ~ +45
Operation Humidity (RH)	10%-90%
Life Span (H)	100,000
Certificates	CE

Product Code: FO-SC-25