LEDUK

Haydos 200W

The Haydos 200W is a IP65 high bay LED with a 26,000 lm output. This luminaire uses a Nichia LED chip with a Meanwell driver creating a high performing durable product. The body is made from cast aluminium and houses a tempered glass diffuser. The Haydos comes supplied with loop suspension mounting as standard but can also be supplied with ceiling or wall bracket.

- Nichia LED chip
- · Meanwell driver
- · Aluminium body and tempered glass diffuser
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

| Dimensions | 383 × 203.5 × 383mm |
|---------------|---------------------|
| Weight | 7.6 kg |
| Voltage | 200-240Vac 50-60Hz |
| Certification | CE, ROHS |
| Warranty | 5 Years |
| IP Rating | IP65 |

Performance

| Colour Rendering | Ra>73 |
|------------------|---|
| Longevity | 50,000 hours |
| System Power | 200 W |
| Exit Lumens | 26000 lm |
| Efficiency | 130 II/cW |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating |

Available options

| 3000K, 4000K, 5000K, 5700K |
|--|
| 50°, 90°, 120° |
| Suspended, Surface |
| No Sensor, Microwave Sensor |
| Fixed Output, 1-10V Dimming, DALI Dimmable |
| Not Required, 3 Hour Facility |
| |

Product Code: HYD-S-200