

LED UK

HAZX Prime Mini

The HAZX Prime Mini luminaire is circular explosion-proof CREE LED floodlight which can be used in Zone 1 & 2 (Gas) and Zone 21 & 22 (Dust). The luminaire has a bowl lens for a glare controlled 180° light distribution. The HAZX Prime Mini is finished with an epoxy powder coating with tempered glass and stainless steel fixings.



- Zone 1 & 2 (Gas) & Zone 21 & 22 (Dust)
- Atex Certified
- CREE LED
- 120° & 180° outputs
- Excellent EMC compatibility
- Dual chamber design for integral gear and LEDs
- Over 60,000 hours life span

General

Dimensions	Ø253 x 305mm
Weight	7.0kg
Installation	Bracket Mounted
Voltage	90-260Vac 50/60Hz
Classification	ExdII CT6 Gb/ExtIII BT85°C Db
Zone	Zone 1 & 2 (Gas) Zone 21 & 22 (Dust)
Warranty	5 Years

Performance

IP rating	IP66
Colour Rendering	Ra>80
Longevity	60,000 hours
System Power	21.3 W 32.1 W 43.2 W
Exit Lumens	2,030 lm 2,996 lm 3,650 lm
Efficiency	95.3 ll/cW 93.3 ll/cW 84.5 ll/cW
Compliance	ATEX Certified

LED UK

HAZX Prime Mini

Available options

Wattage	20W, 30W, 40W
Colour Temperature	3000K, 5000K
Beam Angle	120° (Wide), 180° (Flood)
Lens Cover	Nickel Plated Steel, Stainless Steel
Emergency (Excludes 40W Version)	Not required, 3 Hour Emergency Facility

Product Code: HAZX-PRM-M