Page 1/1

Wattage	10W - 775lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 6000K
Beam Angle	15°, 24°, 36°
Lens	Clear
Dimming	Fixed Output, 1-10V Dimming , DALI Dimmable, Mains DImming, Switch Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour

Central Test, Central Battery System

System Power **Exit Lumens** Efficiency

Available options

Product Code: HST-M

Colour Rendering

Longevity

Compliance

Weight	0.17kg	
Installation	Ceiling Tile Plasterboard	
Voltage	220-240Vac	
Certification	CE, ROHS	
Warranty	5 Years	
Performance		

Ra>82

10W

775lm

77.5 II/cW

SKA Rating

50,000 Hours

Building Regulations

ETL (Energy Technology List) ECA (Enhanced Capital Allowance)

General

Dimensions

Cutout

The heatsink is constructed from o	die-cast aluminium complete with	a aluminium bezel
and reflector recess detail creating	g a glare friendly cut-off which is a	also an aesthetically
pleasing architectural detail.		

- CREE LED Engine
- Cast Aluminium

LEDUK

Hestia Mini

- Instant on no flicker
- · Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference

Ø90 x 87mm

Ø80mm

• Over 50,000 hours life span

The Hestia Mini LED is a 90mm diameter downlight which uses a CREE LED engine.
The heatsink is constructed from die-cast aluminium complete with a aluminium bezel