

The Hestia LED is a 120mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector recess detail creating a glare friendly cut-off which is also an aesthetically pleasing architectural detail.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	Ø120 x 101mm
Cutout	Ø110mm
Weight	0.47kg
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	15W 20W
Exit Lumens	1162 lm 1550 lm
Efficiency	77.5 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	15W - 1162lm, 20W - 1550lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 6000K
Beam Angle	15°, 24°, 36°, 60°
Lens	Polycarbonate
Dimming	Fixed Output, 1-10V Dimming , DALI Dimmable, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: HST-S