

Impact High Output

The IP65 Impact High Output LED is a vapour-proof luminaire with a IK10 Impact Rating which is available in 1500mm. The luminaire body is constructed from GRP and ABS which houses the singular LED board. The lens is part frosted reducing glare from all viewing angles.

- IP65 rated
- IK10 Impact Rating
- 1500mm modules
- 5 year warranty
- 50,000 hours
- Mercury free, No UV or IR
- Instant start and flicker free



General

Dimensions	1500 x 91 x 74mm
Weight	4.5kg 1500mm Module
Installation	Ceiling Surface Ceiling Suspended Wall Surface
Voltage	200-240Vac 50/60Hz
Certification	SAA, TUV, CE, GS, CB, ERP
Warranty	5 Years

Performance

Colour Rendering	Ra>80-85
Longevity	50,000 hours
System Power	62.3 W
Luminous	6230Lm
Efficiency	100 II/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



Impact High Output

Available options

Wattage	60W (1500mm Module)
Colour Temperature	3000K, 4000K, 5000K, 6000K
Mounting Option	Surface, Suspended
Microwave Sensor	Not Required, Microwave Sensor
Cable Entry	Side Entries (IP68 connectors), Rear Entry
Dimming	Fixed Output, 1-10V Dimming, DALI, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, 3 Hour Central Battery

Product Code: IMP