

LED UK

LED 40W-KAS-CL16R-M

Aluminum (AL01070) reflector of good reflection, PMMA lens with high transmittance, special designed PC cover for better lighting effect, wide selection of beam angles. This perfect design highlights optical quality and lighting quality, giving even and soft light, no dark dot, dark area and halo. Simple and elegant design concept, perfectly embodies its stability feature under gentle appearance, great visual comfort due to rear position of light source, Shading angle 30 degree, available in round and square versions. Anti-glare design, meets the standard of UGR19.



- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	140*160mm
Cutout	Ø120-130mm
Installation	Ceiling Tile Plasterboard
Beam Angle	20° 24° 30° 36°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	3 Years

Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	40 W
Exit Lumens	3200 lm
Efficiency	80.0 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating

Available options

Colour	3000K, 4000K, 5000K
Beam Angle	15° Beam, 24° Beam, 30° Beam, 36° Beam, 60° Beam
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable

Product Code: LED 40W-KAS-CL16R-M