

LED UK

Levo Square Mini

Levo Square Mini Trimless Downlight is a 71 x 71mm plaster in luminaire providing a low glare and functional light output along with a seamless architectural installation. The fitting is constructed from die-cast aluminium and is complete with a choice of white, gold or black inner baffle. The fitting is fitted with a Philips LED providing a luminaire luminous flux of 700 lumens. The luminaire may be tilted to a maximum of 30 degrees.

- Philips LED
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Available in a range of beam angles

General

Dimensions	71 x 71 x 103mm
Cutout	72 x 72mm
Weight	0.4kg
Beam Angle	15/24/30/36
Installation	Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years
IP Rating	IP20

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	10.0 W
Exit Lumens	700 lm
Efficiency	70.0 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	10W - 700 lm
Colour	Gold, Black, White
Colour Temperature	2700K, 3000K, 4000K
Beam Angle	15, 24, 30, 36
Lens	Clear
Dimming	Fixed Output, 1-10V Dimming , DALI Dimmable, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: LVS-M

