

## **Levo Square**

Levo Square Trimless Downlight is a  $100 \times 100$ mm plaster in luminaire providing a low glare and functional light output along with a seamless architectural installation. The fitting is constructed from die-cast aluminium and is complete with a choice of white, gold or black inner baffle. The fitting is fitted with a Philips LED providing a luminaire luminous flux of up to 1400 lumens. The luminaire may be tilted to a maximum of 30 degrees.

- Philips LED
- Cast Aluminium
- · Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Available in a range of beam angles



#### General

 $\begin{array}{lll} \textbf{Dimensions} & 100 \times 100 \times 119 \text{mm} \\ \textbf{Cutout} & 102 \times 102 \text{mm} \\ \textbf{Weight} & 0.9 \text{kg} \end{array}$ 

Beam Angle15/24/30/36/60InstallationPlasterboardVoltage220-240VacCertificationCE, ROHSWarranty5 YearsIP RatingIP20



#### **Performance**

 Colour Rendering
 Ra>82

 Longevity
 50,000 hours

 System Power
 15.0 W

 20.0 W

Exit Lumens 1050 lm 1400 lm Efficiency 70.0 ll/cW

Compliance Building Regulations

ETL (Energy Technology List) ECA (Enhanced Capital Allowance)

SKA Rating





# **Levo Square**

### **Available options**

Wattage	15W - 1050 lm, 20W - 1400 lm
Colour	Gold, Black, White
Colour Temperature	2700K, 3000K, 4000K
Beam Angle	15, 24, 30, 36, 60
Lens	Clear
Dimming	Fixed Output, 1-10V Dimming , DALI Dimmable, Mains DImming, Switch Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

**Product Code: LVS**