

Levo Trimless Downlight is 101mm diameter plaster in luminaire providing a low glare and functional light output along with a seamless architectural installation. The fitting is constructed from die-cast aluminium and is complete with a choice of white, gold or black inner baffle. The fitting is fitted with a Philips LED providing a luminaire luminous flux of up to 1400 lumens. The luminaire may be tilted to a maximum of 30 degrees.


- Philips LED
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Available in a range of beam angles

General

Dimensions	Ø101 x 119mm
Cutout	Ø112
Weight	0.6kg
Beam Angle	15/24/30/36/60
Installation	Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years
IP Rating	IP20

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	15.0 W
	20.0 W
Exit Lumens	1050 lm
	1400 lm
Efficiency	70.0 lm/cW
Compliance	Building Regulations
	ETL (Energy Technology List)
	ECA (Enhanced Capital Allowance)
	SKA Rating



Available options

Wattage	15W - 1050 lm, 20W - 1400 lm
Colour	Gold, Black, White
Colour Temperature	2700K, 3000K, 4000K
Beam Angle	15, 24, 30, 36, 60
Lens	Clear
Dimming	Fixed Output, 1-10V Dimming , DALI Dimmable, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: LVO-S