

# LED UK

## Magno Modulus

The Magno Modulus Adjustable LED is an 88mm diameter downlight supplied with a Tridonic Mains Driven LED Module. The luminaire is constructed from die-cast aluminium. The bezel features a concentric rings allowing for a magnetic inner lamp housing which further creates a glare friendly cut-off along with an aesthetically pleasing architectural detail.

- Supplied with Tridonic SLA AC Module
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- 5 Year Guarantee
- 3 Step MacAdam



### General

Dimensions	Ø80mm
Cutout	Ø76mm
Weight	0.5kg
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac 100-240Vac
Certification	CE, ROHS



### Performance

Colour Rendering	Ra>92
Longevity	50,000 hours
System Power	10W
Exit Lumens	700 Lumen
Efficiency	85 lm/W
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

### Available options

Wattage	10 Watt - 700 Lumens
Colour	White, Special RAL Colour
Colour Temperature	2700K, 3000K, 4000K
Beam Angle	24°, 36°
Dimming	Not Required, Mains Dimming
Emergency	Not Available

Product Code: MAG-MODU