

Magno Trimless Twin Engine

The Magno Trimless Twin Adjustable LED provides a twin plate with 2 x 70mm openings. the installation is finished with plaster providing an architectural finish. The fitting is supplied with 2 x high efficiency LED light engines providing up to 2 x 1200 Lumens. The luminaire is constructed from die-cast aluminium. The bezel creates a glare friendly cut-off.

- Supplied with Twin Tridonic SLA DC Light Engines
- · Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- 5 Year Guarantee
- 3 Step MacAdam





General

 $\begin{array}{ll} \textbf{Dimensions} & 200\text{mm x } 100\text{mm x } \text{H}142\text{mm} \\ \textbf{Cutout} & 2\text{ x } \varnothing 70\text{mm (}40\text{mm Centres)} \\ \end{array}$

Weight 1.2kg
Installation Ceiling Tile
Plasterboard
Voltage 220-240Vac

Certification CE, ROHS Warranty 5 Years



Performance

 Colour Rendering
 Ra>82

 Longevity
 50,000 hours

 System Power
 2 x 8.8W

 2 x 12.2W

 Exit Lumens
 2 x 700 Lumen

 2 x 1200 Lumen

 Efficiency
 101.0 II/cW

 104.0 II/cW

Compliance Building Regulations

ETL (Energy Technology List) ECA (Enhanced Capital Allowance)

SKA Rating

Available options

Wattage	2 x 8 Watt - 700 Lumens, 2 x 12 Watt - 1200 Lumens
Colour	White, Special RAL Colour
Colour Temperature	2700K, 3000K, 4000K
Beam Angle	24°, 36°
Dimming	Not Required, 1-10V Dimming, Dali Dimmable, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour Facility

Product Code: MTT-ENGI