

MI Series - 6.0 mm Pixel Pitch

6.0 mm Pixel Pitch, Lightweight full colour LED Screen display

- Cabinet weight is only 8.3 kg, depth 73 mm, decreasing the transportation cost and the intensity of labour
- Super thin power supply inside; Quiet fan design, excellent heat dissipation, noiseless
- Refresh rate > 800HZ, 2 times higher than the regular screen, suitable for any occasion which requires much higher display capability
- The high polymer flexible mask can be pulled off directly from the cabinet, which makes the maintenance much more convenient
- Signal & power aviation connectors are water & dust proof, stable and reliable
- Cushion under the cabinet can protect the modules from being damaged
- Super-light aluminium alloy connectors are durable and artistic



Model	MI-SC-6
Pixel Pitch (mm)	6
Physical Density (dot/m²)	27,777
LED Configuration	1R1G1B
LED Type	SMD3528
Module Size (mm x mm)	240 x 240
Module Resolution (PX x PX)	40 x 40
Power Consumption (W)	60
Drive Mode:	Constant Current Drive
Horizontal Viewing Angle (Deg)	140
Vertical Viewing Angle (Deg)	140
Brightness (cd/m²)	1,200
Grey Scale	16 Bit
Refresh Rate (Hz)	800/1920
Cabinet Resolution (PX x PX)	80 x 80
Cabinet Max Power Consumption (W)	300
Cabinet Avg Power Consumption (W)	120
Cabinet Size (mm x mm)	480 x 480
Cabinet Weight (kg)	7.5
Cabinet Thickness	73

LED UK

MI Series - 6.0 mm Pixel Pitch

(mm)	
Cabinet Material	Aluminium
Colour	281tn
Input Voltage	AC 110V~220V +/- 10%
Refresh Frame Frequency (Hz)	60
Protection Level	IP43
Working Environemt	Indoor
Working Temperature (°C)	-20 ~ +40
Operation Humidity (RH)	10%-90%
Life Span (H)	100,000
Vertical Hanging Quantity	MAX 20
Certificates	CE ETL TUV-EMC

Product Code: MI-SC-6