

Good visual comfort with mini optical components. No dark dot due to its special configuration of the optical system which makes precise round light distribution. No limitation to a fixed frame, but more choices for customisation. 0°-25°vertical axis adjustable design for your convenience.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	Ø90 x 115mm
Cutout	Ø75mm
Installation	Ceiling Tile Plasterboard
Beam Angle	15° 30°
Voltage	AC220-240V/AC100-240V
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	8W 10W 12W 15W
Exit Lumens	640lm 800lm 960lm 1200lm
Efficiency	80.0 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



Available options

Wattage	8W - 640lm, 10W - 800lm, 12W - 960lm, 15W - 1200lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 5000K
Beam Angle	15° Beam, 30° Beam
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: MIR-S