


Onyx

Onyx is a surface mounted continuous extrusion luminaire available in 1000mm to 5000mm linear lengths or as prepared bespoke fitting for your project requirements. Onyx is supplied with a Opal, Frosted or Clear diffuser which makes it ideal for architectural spaces. Onyx Opal diffuser provides a dot free appearance across all wattages making the fitting suitable to be on display as an architectural feature. Onyx is available as fixed output, dimmable or colour changing RGB.

- Aluminium profile
- Opal, Frosted or Clear polycarbonate diffuser
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Supplied with Remote LED Driver
- Supplied with end caps & flying lead



General

|               |   |
|---------------|---|
| Dimensions    | 19.6 x 19.5 x 1000mm to 5000mm<br>35 x 25.4 Besoke Requirement (100mm Cuts) |
| Weight        | 0.7 kg per metre  |
| Beam Angle    | 90°   |
| Installation  | Surface Mounted   |
| Voltage       | 220-240Vac  |
| Certification | CE, ROHS  |
| Warranty      | 3 Years   |

Performance

|                  |  |
|------------------|--|
| Colour Rendering | Ra>80  |
| Longevity        | 50,000 hours   |
| System Power     | 5.00 W<br>10.0 W<br>15.0 W   |
| Lumens           | 490 lm<br>950 lm<br>1350 lm  |
| Compliance       | Building Regulations<br>ETL (Energy Technology List)<br>ECA (Enhanced Capital Allowance)<br>SKA Rating |

Available options

|                    |   |
|--------------------|---|
| Length             | 1000mm, 2000mm, 3000mm, 4000mm, 5000mm, Bespoke |
| Body Finish        | Aluminium, White, Black                         |
| Colour Temperature | 2700K, 3000K, 4000K, 5000K, RGB                 |
| Diffuser           | Opal, Frosted, Clear                            |
| Wattage            | 5W, 10W, 15W, 5W (RGB)                          |
| Dimming            | Fixed Output, DALI, DMX                         |

Product Code: ONX