

Phobos

The Phobos is a flexible surface downlight, it's adjustable angle lets you transform your lighting to suit your requirements. The luminaire has a 360° Rotation, and 0-90° tilt. It is available in Black, White, or Silver finish.

- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




General

Dimensions	196 x 160 x 96mm
Installation	Ceiling Surface
Beam Angle	15° 20° 30° 36°
Voltage	45° AC220-240V
Certification	CE, ROHS
Warranty	5 Years



Performance

Colour Rendering	Ra>80/90	
Longevity	50,000 hours	
System Power	30 W	
	35 W	
	40 W	
	50 W	
Exit Lumens	2,700 lm	
	3,150 lm	
	3,600 lm	
	4,200 lm	
Efficiency	90.0 II/cW	
•	90.0 II/cW	
	90.0 II/cW	
	84.0 II/cW	
Compliance	Building Regulations	
•	ETL (Energy Technology List)	
	ECA (Enhanced Capital Allowance)	
	SKA Rating	





Phobos

Available options

Wattage	30W - 2700 lm, 35W - 3150 lm, 40W - 3600 lm, 50W - 4200 lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 5000K
Beam Angle	15°, 20°, 30°, 36°, 45°
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming

Product Code: PHB