

LED UK

Pike IP

The Pike IP LED is a 65mm diameter downlight which uses a CREE LED engine. The Pike IP has a frosted lens and an IP44 rating. The heatsink features adjustable fold-out arms which allows the Pike to be installed with ease.


- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	Ø65 x 79mm
Cutout	Ø55mm
Weight	1.1kg
Beam Angle	15° 24° 30° 36°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	8W
Exit Lumens	593 Lumens
Efficiency	74.1 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



LEDUK

Pike IP

Available options

Wattage	8W - 593 lm
Colour	White, Special RAL Colour
Colour Temperature	2700K, 3000K, 4000K, 5000K
Beam Angle	15°, 24°, 30°, 36°
Lens	Frosted Diffuser
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: PKE-S