


## Pike

The Pike LED is a 65mm diameter downlight which uses a CREE LED engine. The heatsink features adjustable fold-out arms which allows the Pike to be installed with ease.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

### General

<b>Dimensions</b>	Ø65 x 79mm
<b>Cutout</b>	Ø55mm
<b>Weight</b>	1.1kg
<b>Beam Angle</b>	15° 24° 30° 36°
<b>Installation</b>	Ceiling Tile Plasterboard
<b>Voltage</b>	220-240Vac
<b>Certification</b>	CE, ROHS
<b>Warranty</b>	5 Years



### Performance

<b>Colour Rendering</b>	Ra>82
<b>Longevity</b>	50,000 hours
<b>System Power</b>	8W
<b>Exit Lumens</b>	593 Lumens
<b>Efficiency</b>	74.1 lm/cW
<b>Compliance</b>	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	8W - 593 lm
Colour	White, Special RAL Colour
Colour Temperature	2700K, 3000K, 4000K, 5000K
Beam Angle	15°, 24°, 30°, 36°
Lens	Clear
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: PKE-S