

## PO Series - 20.0 mm Pixel Pitch

20.0 mm Pixel Pitch, IP65 Outdoor LED Screen display

- High-quality, ultra-light cabinet with concealed side locks
- 140° horizontal & vertical viewing angle, flatness
- High quality anti-collision foam, resistant to shock
- Macromolecular flexible mask with glareless surface and better contrast ratio
- Unique joint structure for free assembly and dismantlement of different display dimension
- Back cover lock system to avoid faulty operation of the amateur



<b>Model</b>	<b>PO-SC-20</b>
<b>Pixel Pitch (mm)</b>	20
<b>Physical Density (dot/m<sup>2</sup>)</b>	2,500
<b>LED Configuration</b>	1R1G1B
<b>LED Type</b>	DIP346
<b>Module Size (mm x mm)</b>	320 x 160
<b>Module Resolution (PX x PX)</b>	16 x 8
<b>Drive Mode:</b>	Constant Current Drive
<b>Horizontal Viewing Angle (Deg)</b>	120
<b>Vertical Viewing Angle (Deg)</b>	70
<b>Brightness (cd/m<sup>2</sup>)</b>	6,000-7,000
<b>Grey Scale</b>	16 Bit
<b>Refresh Rate (Hz)</b>	1,200
<b>Cabinet Resolution (PX x PX)</b>	64 x 48
<b>Cabinet Max Power Consumption (W)</b>	1,000
<b>Cabinet Avg Power Consumption (W)</b>	400
<b>Cabinet Size (mm x mm)</b>	1,280 x 960
<b>Cabinet Weight (Kg)</b>	70(steel) 55 (aluminium)
<b>Cabinet Thickness (mm)</b>	150
<b>Cabinet Material</b>	Steel/Aluminium
<b>Colour</b>	281tn
<b>Input Voltage</b>	AC 110V~220V +/- 10%

## PO Series - 20.0 mm Pixel Pitch

---

<b>Refresh Frame Frequency (Hz)</b>	50/60
<b>Protection Level</b>	IP65
<b>Working Environment</b>	Outdoor
<b>Working Temperature (°C)</b>	-20 ~ +40
<b>Operation Humidity (RH)</b>	10%-90%
<b>Life Span (H)</b>	100,000
<b>Standard</b>	FIFA/EUSA/V2.0
<b>Certificates</b>	TUV-EMC CE

**Product Code: PO-SC-20**