

# LED UK

## Quadrus Trimless

---

Quadrus Square Trimless LED is a 102mm x 102mm downlight for plaster in ceiling. The fitting utilises a Cree SMD LED Array. The heatsink is constructed from die-cast aluminium reflector and the reflector is finished in white, black or gold. The downlight is available in outputs from 975lm to 1950lm and as standard is rated IP20.

- CREE SMD LED
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



### General

Dimensions	102 x 102mm
Cutout	102 x 102mm
Weight	0.8kg
Beam Angle	15°/20°/30°/36°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years
IP Rating	IP20

### Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	15.0 W 20.0 W 30.0 W
Exit Lumens	975 lm 1,237 lm 1950 lm
Efficiency	65.00 lm/cW 61.85 lm/cW 65.00 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

# LED UK

## Quadrus Trimless

---

### Available options

Wattage	15W , 20W, 30W
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 6000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: QUT