

# LED UK

## Sirius Max


The Sirius Max LED is a 230mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The heatsink features adjustable fold-out arms which allows the Sirius Max to be installed with ease. The downlight is available in outputs from 1500lm to 3300lm. The luminaire is supplied with an open bezel as standard.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




### General

Dimensions	Ø230 x 99mm
Cutout	Ø200-210mm
Weight	1.8kg
Beam Angle	60°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years



### Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	20W 25W 30W 35W 40W
Exit Lumens	1514lm 2172lm 2502lm 2863lm 3300lm
Efficiency	75.7 ll/cW 86.9 ll/cW 83.4 ll/cW 81.8 ll/cW 82.5 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



Available options

Wattage	20W - 1514lm, 25W - 2172lm, 30W - 2502lm, 35W - 2863lm, 40W - 3300lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 6000K
Lens	Clear Lens, Frosted
Dimming	Fixed Output, 1-10V Dimmable, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility

Product Code: SRS-X