

Sirius Mini (OLD)


The Sirius Mini LED is a 110mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The heatsink features adjustable fold-out arms which allows the Sirius Mini to be installed with ease. The downlight is available in outputs from 630lm to 1350lm.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




General

Dimensions	Ø110 x 53mm
Cutout	Ø95mm
Weight	0.9kg
Beam Angle	60°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years



Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	7 W 9 W 12 W 15 W
Exit Lumens	630 lm 810 lm 1080 lm 1350 lm
Efficiency	90.0 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating



Available options

Wattage	7W - 630 lm, 9W - 810 lm, 12W - 1080 lm, 15W - 1350 lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 6000K
Lens	Clear Lens
Dimming	Fixed Output, 1-10V Dimmable, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility

Product Code: SRS-M