

LED UK

Sirius OLD


The Sirius LED is a 190mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The heatsink features adjustable fold-out arms which allows the Sirius to be installed with ease. The downlight is available in outputs from 1300lm to 2500lm.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




General

Dimensions	Ø190 x 98mm
Cutout	Ø170mm
Weight	1.1kg
Beam Angle	60°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years



Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	15.9 W 20.6 W 25.4 W 30.8 W
Exit Lumens	1,375 lm 1,765 lm 2,156 lm 2,591 lm
Efficiency	86.5 ll/cW 85.7 ll/cW 84.9 ll/cW 84.1 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



Available options

Wattage	15W - 1300 lm, 20W - 1600 lm, 25W - 2200 lm, 30W - 2500 lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 6000K
Lens	Clear Lens
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: SRS-S