Page 1/1

LEDUK Trimless IP65

The Trimless IP65 LED provides an exposed 70mm diameter aperture to be finished with plaster providing a trimless, clean architectural finish. It is supplied with a 7Watt GU10 LED lamp. The luminaire is constructed from die-cast aluminium. The fitting recess provides a glare friendly cut-off.

- GU10 Lamp
- Cast Aluminium
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 30,000 hours life span
- Magnetic Lamp Retention System
- Rated IP65

General

Dimension Cutout Weight Installation Voltage	Ø120mm x H142mm Ø70mm 0.4kg Plasterboard 220-240Vac 100-240Vac
Certification	CE, ROHS
Warranty	3 Years

Performance

Colour Rendering Longevity System Power Exit Lumens Efficiency Compliance

Ra>82 30,000 hours
7W GU10
600 Lumen
85.71 II/cW
Building Regulations
ETL (Energy Technology List)
ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	7 Watt - 600 Lumens
Colour	White, Special RAL Colour
Colour Temperature	2700K, 3000K, 4000K
Beam Angle	36°
Dimming	Not Required, Mains Dimming
Emergency	Not Required, 3 Hour Facility

Product Code: TLS-GU10

