

LED UK

Triton




The Triton LED modular 600 x 600mm luminaire has three opal rectangular polycarbonate diffusers which gives the luminaire a distinctive bold style. The body is made from powder coated steel finished in white with all gear being housed internally. The luminaire is powered by three Philips LED boards allowing the product to achieve an efficiency of up to 80lm/cW with a lifespan of over 50,000 hours.



- High transmittant frosted diffuser
- White powdercoat finish
- Philips LED boards
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	595 x 595 x 45mm
Weight	4.9kg
Installation	Recessed 24mm T-Grid Recessed 15mm T-Grid
Voltage	220-240Vac 50/60Hz
Certification	SAA, TUV, CE, GS, CB, ERP
Warranty	5 Years



Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	32.2 W 37.5 W 48.7 W
Exit Lumens	2612 lm 2988 lm 3789 lm
Efficiency	81.1 lm/cW 79.7 lm/cW 77.8 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	30W - 2400 lm, 36W - 2900 lm, 45W - 3600 lm
Colour Temperature	3000K, 4000K, 6500K
Mounting Option	Lift and tilt, Offer up
Dimming	Fixed output, 1-10V Dimming, DALI Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: TRI