

Union Floodlight

The floodlight is constructed from high grade cast aluminium finished with a zinc coating for interior and exterior use. The highly efficient Cree LED light source creates exit lumen packages ranging from 3600 to 32400lm

- Cree LED chips
- 50,000hours
- 3000K, 4000K & 6000K
- DALI / 0-10Vdc dimming
- Photocell sensor system
- Built-in surge protection
- Built-in thermal protection
- Maintenance free
- Mercury free, No UV or IR
- Instant start and flicker free
- Patent multi-function design
- Up to 10 year warranty

General

| | |
|----------------------|---------------------------|
| Dimensions | 360 x 358 x 187mm |
| Weight | 8 kg |
| Certification | SAA, TUV, CE, GS, CB, ERP |
| Warranty | Up to 10 Years |

Performance

| | |
|------------------------------|--|
| Operating Temperature | -40°C - 60°C |
| Colour Rendering | Ra>80 |
| Longevity | 50,000 hours |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating |

Available options

| | |
|---------------------------|---|
| Wattage | 30W, 60W, 90W, 120W, 150W, 180W, 210W, 270W |
| Colour Temperature | Warm White (3000K), Neutral White (4000K), Cool White (6000K) |
| Beam Angle | 60°, 120°, 140 X 60° |
| IP Rating | IP65, IP67 |
| Mounting Option | Pendent, Pole, Bracket |
| Dimming | Fixed Output, 1-10V Dimmable, DALI Dimmable |
| Photocell | Not Required, Microwave Sensor, Photocell |
| Input | 80 - 315Vac, 80 - 400Vdc |
| Light Distribution | No Beam Control, Lens Guard |

Product Code: UNI

