

## **Union Max Projector**

The Single Lens Projector is constructed from high grade cast aluminium finished with a zinc coating for interior and exterior use. The highly efficient Cree LED light source creates exit lumen packages ranging from 24,000 to 84,000lm.

- Cree LED chips
- 50,000hours
- 3000K, 4000K & 6500K
- DALI / 0-10Vdc dimming
- Photocell sensor system
- Built-in surge protection
- Built-in thermal protection
- · Maintenance free
- Mercury free, No UV or IR
- · Instant start and flicker free
- Patent multi-function design
- Up to 10 year warranty




## General


Dimensions	466 x 388 x 471mm
Weight	19.0 kg
Certification	SAA, TUV, CE, GS, CB, ERP
Warranty	Up to 10 Years



<b>Operating Temperature</b>	-40°C - 60°C
Colour Rendering	Ra>80
Longevity	50,000 hours
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating









## **Union Max Projector**

## **Available options**

Wattage	300W, 400W, 500W, 600W, 700W
Colour Temperature	Warm White (3000K), Neutral White (4000K), Cool White (6000K)
Beam Angle	15°, 20°, 30°
IP Rating	IP67
<b>Mounting Option</b>	Pendent, Pole, Bracket
Dimming	Fixed Output, 1-10V Dimmable, DALI Dimmable
Photocell	Not Required, Microwave Sensor, Photocell
Input	110-480Vac
Light Distribution	No Beam Control, Horizontal Hood, Lens Guard, Horizontal Hood + Lens Guard

**Product Code: UNI**