

Viridi Recessed Uplight


The Verdi is a 85mm diameter recessed uplight available 7 or 9 watt. It is constructed from stainless steel and tempered glass and is rated IP68. The fitting is supplied with a polycarbonate mounting sleeve and fitted with a low glare honeycomb louvre.

- IP68 Rated
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




General

| | |
|----------------------|--------------------------|
| Dimensions | Ø85 x 95mm |
| Cut Out | Ø72mm |
| Beam Angle | 15° 24° 36° 45° |
| Voltage | 24V |
| Certification | CE, ROHS |



Performance

| | |
|-------------------------|--------------------------------------------------------------------------------------------------------|
| Colour Rendering | Ra>80 |
| Longevity | 50,000 hours |
| System Power | 7W 9W |
| Exit Lumens | 450 Lm 611 Lm |
| Efficiency | 50 l/cw 68 l/cw |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating |



Available options

| | |
|---------------------------|---------------------------------------------------------------------------|
| Wattage | 7 Watt, 9 Watt |
| Colour | Stainless Steel |
| Colour Temperature | 2700K, 3000K, 4000K, 5000K |
| Diffuser | Honeycomb |
| Beam Angle | 15° Beam, 24° Beam, 36° Beam, 45° Beam |
| Dimming | Not Required, 1-10V Dimming, DALI Dimmable, Mains Dimming, Switch Dimming |
| Emergency | Not Available |

Product Code: VRU