

LED UK

Vista 1260

Vista 1260 is a 1200 x 600 Lay in side lit recessed LED Modular with opal diffuser. The luminaire is designed for lift and tilt installation onto a 15mm or a 24mm Tee Grid. The Vista LED panel light is an environmentally friendly LED solution assembled from aluminium and a high efficiency PMMA diffuser which provides a uniformed, low glare and dot free distribution of light.

- High transmittant opal lens
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Remote LED Driver

General

| | |
|---------------|----------------------------|
| Dimensions | 1195 x 595 x 10mm |
| Weight | 4.0kg |
| Installation | Recessed 16 or 24mm T-Grid |
| Voltage | 85-265Vac 50/60Hz |
| Certification | SAA, TUV, CE, GS, CB, ERP |
| Warranty | 5 Years |
| IP Rating | IP40 |

Performance

| | |
|------------------|--|
| Colour Rendering | Ra>80 |
| Longevity | 50,000 hours |
| System Power | 60.0W |
| Lumens | 72.0W 6000 lm |
| Efficiency | 7200 lm 100.00 ll/cW |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating |

Available options

| | |
|--------------------|--|
| Wattage | 60W (6000 lm), 72W (7000 lm) |
| Colour Temperature | 3000K, 4000K, 6000K |
| Mounting Option | Lift and tilt |
| Dimming | Fixed output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming |
| Emergency | Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System |

Product Code: VTA-1260

