LEDUK Vista 600

Vista 600 is a 600 x 600 side lit LED Modular with opal diffuser. The luminaire is designed for either lift and tilt installation onto a 15mm or a 24mm Tee Grid, suspended using suspension kits or surface mounting with the use of a specially designed surface mounted frame. The Vista LED panel light is an environmentally friendly LED solution assembled from aluminium and a high efficiency PMMA diffuser which provides a uniformed, low glare and dot free distribution of light.

- High transmittant opal lens
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Remote LED Driver

General

Dimensions Weight Installation Voltage Certification Warranty IP Rating 595 x 595 x 10mm 3.0kg Recessed 16 or 24mm T-Grid 85-265Vac 50/60Hz SAA, TUV, CE, GS, CB, ERP 5 Years IP40



Performance

Colour Rendering Longevity System Power	Ra>80 50,000 hours 40.0 W
Lumens	45.0 W 4000 lm
Efficiency Compliance	4500 lm 100.00 ll/cW Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance)

Available options

Wattage	40W (4000 Lm), 45W (4500 Lm)
Colour Temperature	3000K, 4000K, 6000K
Mounting Option	Lift and tilt, Suspended, Surface
Dimming	Fixed output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

SKA Rating

Product Code: VTA-600



10