

Wallex is a surface mounted wall continuous extrusion luminaire available in 1000mm to 5000mm linear lengths or as prepared bespoke fitting for your project requirements. Wallex is supplied with a Opal, Frosted or Clear diffuser which makes it ideal for architectural spaces. Wallex Opal diffuser provides a dot free appearance across all wattages making the fitting suitable to be on display as an architectural feature. Wallex is available as fixed output, dimmable or colour changing RGB.

- Aluminium profile
- Opal, Frosted or Clear polycarbonate diffuser
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Supplied with Remote LED Driver
- Supplied with end caps & mounting clip accessories




General

| | |
|---------------|--------------------------|
| Dimensions | Height 35mm x Width 42mm |
| Weight | 0.8 kg per metre |
| Beam Angle | 60° |
| Installation | Surface Mounted |
| Voltage | 220-240Vac |
| Certification | CE, ROHS |
| Warranty | 3 Years |



Performance

| | |
|------------------|----------------------------------|
| Colour Rendering | Ra>80 |
| Longevity | 50,000 hours |
| System Power | 5.00 W |
| | 10.0 W |
| | 15.0 W |
| | 29.0 W |
| Lumens | 490 lm |
| | 950 lm |
| | 950 lm |
| | 1350 lm |
| Compliance | Building Regulations |
| | ETL (Energy Technology List) |
| | ECA (Enhanced Capital Allowance) |
| | SKA Rating |



Available options

| | |
|--------------------|--|
| Length | 1000mm, 2000mm, 3000mm, 4000mm, Bespoke |
| Body Finish | Aluminium, White, Black |
| Colour Temperature | 2700K, 3000K, 4000K, 6000K, RGB, RGBW |
| Diffuser | Opal, Frosted, Clear |
| Wattage | 5W, 7.2W, 10W, 15W |
| Dimming | Fixed Output, 1-10V Dimming, DALI Dimmable, Mains Dimming, Switch Dimming, DMX |

Product Code: WEX