

12/15W KAS-TL10R-A-6612

The fitting is equipped with an accessory-holder ring. Color filters, glass filter, PMMA filter are available and can be easily attached and replaced. Simple & delicate look with slim body. 360° Rotation, and 0°-90° tilt, easy to turn and highlight what you want to.

- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



Dimensions	D66*W180*H185mm
Installation	Track Lighting
Beam Angle	20° 24° 36° 45°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	3 Years



Performance

Colour Rendering	Ra>80/90
Longevity	50,000 hours
System Power	12 W 15 W
Exit Lumens	960 lm 1200 lm
Efficiency	80.0 II/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating

Available options

Wattage	12W - 960 lm, 15W - 1200 lm
Beam Angle	20°, 24°, 36°, 45°
Colour	3000K, 4000K, 5000K
Base Colour	White, Black
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable

Product Code: 12/15W KAS-TL10R-A-6612