8/10W KAS-BL10R-308

Narrow trim full-closed series, with the driver fixed inside. Its window design makes It well-ventilated. White trim integrates the light with ceiling, clean and fashionable. Full-closed style with window design achieves active heat dissipation. The installation clips protect the ceiling and offer a convenient and easy installation. The mini cap on the bottom of the heatsink ensures that safety standards are met.



- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	93mm*93mm*135mm
Cut Out	85mm*85mm
Installation	Recessed
Beam Angle	15° 20° 30° 36° 60°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	3 Years

Performance

Colour Rendering	Ra>80/90
Longevity	50,000 hours
System Power	8 W 10 W
Exit Lumens	640 lm 800 lm
Efficiency	80.0 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating

Available options

Wattage	8W -640 lm, 10W - 800 lm
Beam Angle	20°, 24°, 30°, 36°, 60°
Colour	3000K, 4000K, 5000K
Base Colour	White, Iron Gray
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable

Product Code: 8/10W KAS-BL10R-308