

Alta Mini


The Alta Mini LED is a 90mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The bezel features a 40mm recess detail creating a glare friendly cut-off which is also an aesthetically pleasing architectural detail. The Alta Mini is available in a 750lm outputs with 15°, 24°, 30° and 36° beam angle options and is rated IP20.

- CREE LED Engine
- Cast Aluminium
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




General

Dimensions	Ø90mm x 100mm
Cutout	Ø80mm
Weight	0.2kg
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years



Performance

Colour Rendering	Ra>82
UGR	<19
MacAdam Ellipse	3 Step
System Power	10 W
Exit Lumens	750lm
Efficiency	75.0 II/cW
Longevity	50,000 hours
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating





Alta Mini

Available options

Wattage	10W - 750lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 5000K
Beam Angle	15° Beam, 24° Beam, 30° Beam, 36° Beam
Lens	Clear
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: ALT-M-F