

Aurora

The Aurora LED is a 92mm diameter tracklight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium housing and reflector. The luminaire is constructed from die cast aluminium and has a 350° swivel arm. The body can rotate 180° from the swivel arm. The Aurora is available in 2210lm and 2926lm outputs with multiple beam angle options. The downlight is supplied with an open anti dazzle reflector as standard.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	Ø100 x 135 x 208mm
Swivel	350°
Weight	1kg
Installation	Track Integration
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	30 W 35 W
Exit Lumens	2210 lm 2926 lm
Efficiency	63.14 lm/cW 83.60 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	30W - 2210 lm, 35W - 2926 lm
Colour	3000K, 4000K
Beam Angle	15° Beam, 24° Beam, 30° Beam, 36° Beam, 45° Beam
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable, Mains Dimming

Product Code: AUR