

The Connex is a 130mm diameter downlight which utilises a Philips LED Module. The heatsink is constructed from die-cast aluminium complete with a either a white or brushed aluminium bezel. The heatsink features sprung arms which allows the fitting to be installed with ease.

- Philips LED Module
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	Ø130 x 99mm
Cutout	Ø110mm
Weight	1.3kg
Beam Angle	40°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years
IP Rating	IP54

Performance

Colour Rendering	Ra>80
Longevity	L80 / B20 @ 50,000 hours
System Power	18W
Exit Lumens	1950 Lm
Efficiency	108 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	18W
Base Colour	Aluminium (Brushed), White
Colour Temperature	2700K, 3000K, 4000K, 5000K
Lens	Clear
Dimming	Fixed Output, DALI
Emergency	Not Required, 3 Hour Facility, 3 Hour Central Test

Product Code: CNX-S